

# Outdoor Dome Camera Line Up


## 2MP Analogue HD (AHD / TVI / CVI / CVSB)

Type	Image	Model Number	Image Sensor	Video Output	Lens	Max. Resolution	IR LED	Noise Reduction	Coaxitron	Power Source	OSD	IP Rate	Size(mm)
Indoor Dome (100mm dia.)		JPDF-AHE100L24	1/2.9" Sony CMOS	DC12V	3.6mm	1920 X 1080	24pcs	2D + 3DNR, D-WDR, Defog	UTC	12VDC	-	-	110 X 95
Indoor Dome (100mm dia.)		JPDF-AHE100	1/2.9" Sony CMOS	DC12V	3.6mm	1920 X 1080	-	2D + 3DNR, D-WDR, Defog	UTC	12VDC	-	-	110 X 95
Vandal Dome		JVDV-AH300L20	1/2.9" Sony CMOS	DC12V	2.8~11mm	1920 X 1080	20pcs	2D + 3DNR, D-WDR, Defog	UTC	12VDC	Built in	IP66	144 X 100
Vandal Dome		JVDV-AH300	1/2.9" Sony CMOS	DC12V	2.8~11mm	1920 X 1080	-	2D + 3DNR, D-WDR, Defog	UTC	12VDC	Built in	IP66	144 X 100
Vandal Dome		JEDV-AH500L35	1/2.9" Sony CMOS	DC12V	2.8~11mm	1920 X 1080	35pcs	2D + 3DNR, D-WDR, Defog	UTC	12VDC	Built in	IP66	135 X 98.85
Vandal Dome		JEDF-AH350L24	1/2.9" Sony CMOS	DC12V	3.6mm	1920 X 1080	24pcs	2D + 3DNR, D-WDR, Defog	UTC	12VDC	Built in	IP66	93 X 80



## 2MP ALL IN ONE (EX-SDI / AHD / TVI / CVI / CVSB)

Type	Image	Model Number	Image Sensor	Video Output	Lens	Max. Resolution	IR LED	Noise Reduction	Coaxitron	Power Source	OSD	IP Rate	Size(mm)
Vandal Dome		JVDV-AE300L20	1/2.9" Sony CMOS	DC12V	2.8~11mm	1920 X 1080	20pcs	2D + 3DNR, D-WDR, Defog	UTC	12VDC	Built in	IP66	144 X 100
Vandal Dome		JVDV-AE300	1/2.9" Sony CMOS	DC12V	2.8~11mm	1920 X 1080	-	2D + 3DNR, D-WDR, Defog	UTC	12VDC	Built in	IP66	144 X 100
Vandal Dome		JEDV-AE500L35	1/2.9" Sony CMOS	DC12V	2.8~11mm	1920 X 1080	35pcs	2D + 3DNR, D-WDR, Defog	UTC	12VDC	Built in	IP66	135 X 98.85
Vandal Dome		JEDF-AE350L24	1/2.9" Sony CMOS	DC12V	3.6mm	1920 X 1080	24pcs	2D + 3DNR, D-WDR, Defog	UTC	12VDC	Built in	IP66	93 X 80



## ALL IN ONE 1/2" Series (EX-SDI 1.0 / EX-SDI 2.0 / AHD / TVI / CVI / CVBS)

Type	Image	Model Number	Image Sensor	Video Output	Lens	Max. Resolution	IR LED	Noise Reduction	Coaxitron	Power Source	OSD	IP Rate	Size(mm)
Vandal Dome		JVDV-2A650	1/2" Sony CMOS (IMX-385)	DC12V	3.6~10mm Motorized	1920 X 1080	30pcs	2D + 3DNR, REAL WDR, Defog	UTC	12VDC	Built in	IP66	150 X 110

## 1/3" 2MP SONY Xarina EXMOR IP Camera Series

Type	Image	Model no.	Image Sensor	Video Compression	Lens	Max. Resolution	Max. Frame Rate	IR	Noise Reduction	Audio Direction	Audio Codec (Optional)	Power Source	Local Storage (Optional)
Outdoor Fixed IR Vandal		JVDV-2IP650	1/2.8" Sony Exmor CMOS Sensor (IMX322)	H.264 & MJPEG Triple Stream	3.6mm	1920x1080	H.264 : 25, 30fps/1080p, M-JPEG : 25, 30fps/VGA	30pcs	2D+3DNR, D-WDR, Defog, Corridor mode	Full Duplex	Two way(G.711) - Optional	PoE(IEEE802.3af), 12VDC	Built in (Upto 128GB)
Outdoor Motorized IR Vandal		JVDMV-2IP650L30	1/2.8" Sony Exmor CMOS Sensor (IMX322)	H.264 & MJPEG Triple Stream	2.8~12mm Motorized	1920x1080	H.264 : 25, 30fps/1080p, M-JPEG : 25, 30fps/VGA	30pcs	2D+3DNR, D-WDR, Defog, Corridor mode	Full Duplex	Two way(G.711) - Optional	PoE(IEEE802.3af), 12VDC	Built in (Upto 128GB)

## 1/3" 3MP SONY Xarina STARVIS IP Camera Series

Type	Image	Model no.	Image Sensor	Video Compression	Lens	Max. Resolution	Max. Frame Rate	IR	Noise Reduction	Audio Direction	Audio Codec (Optional)	Power Source	Local Storage (Optional)
Outdoor Fixed IR Vandal		JVDV-3IP650	1/2.8" Sony Starvis CMOS Sensor (IMX124)	H.264 & MJPEG Triple Stream	3.6mm	2048x1536	H.264 : 25, 30fps/1080p, M-JPEG : 25, 30fps/VGA	30pcs	2D+3DNR, D-WDR, Defog, Corridor mode	Full Duplex	Two way(G.711) - Optional	PoE(IEEE802.3af), 12VDC	Built in (Upto 128GB)
Outdoor Motorized IR Vandal		JVDMV-3IP650L30	1/2.8" Sony Starvis CMOS Sensor (IMX124)	H.264 & MJPEG Triple Stream	2.8~12mm Motorized	2048x1536	H.264 : 25, 30fps/1080p, M-JPEG : 25, 30fps/VGA	30pcs	2D+3DNR, D-WDR, Defog, Corridor mode	Full Duplex	Two way(G.711) - Optional	PoE(IEEE802.3af), 12VDC	Built in (Upto 128GB)