




# Box Camera Line Up


## ✓ 2MP Analogue HD (AHD / TVI / CVI / CVSB)

Type	Image	Model Number	Image Sensor	Video Output	Lens	Max. Resolution	IR LED	Noise Reduction	Coaxitron	Power Source	OSD	IP Rate	Size(mm)	ETC
Box Standard		JBX-AH950	1/2.9" Sony CMOS	DC12V	-	1920 X 1080	-	2D + 3DNR. D-WDR Defog	UTC	12VDC	Built in	-	120 X 65 X 60	
Box Standard		JBX-AH990DU	1/2.8" Sony CMOS	DC12V	-	1920 X 1080	-	2D + 3DNR. D-WDR Defog	UTC	12VDC	Built in	-	59.77 X 63.5 X 97.5	<b>Dual Video Out : AHD &amp; CVBS at the same time</b>


## ✓ 2MP ALL IN ONE (EX-SDI / AHD / TVI / CVI / CVSB)

Type	Image	Model Number	Image Sensor	Video Output	Lens	Max. Resolution	IR LED	Noise Reduction	Coaxitron	Power Source	OSD	IP Rate	Size(mm)	ETC
Box Standard		JBX-AE950	1/2.9" Sony CMOS	DC12V	-	1920 X 1080	-	2D + 3DNR. D-WDR Defog	UTC	12VDC	Built in	-	120 X 65 X 60	


## ✓ ALL IN ONE 1/2" Series (EX-SDI 1.0 / EX-SDI 2.0 /AHD / TVI / CVI / CVBS)

Type	Image	Model Number	Image Sensor	Video Output	Lens	Max. Resolution	IR LED	Noise Reduction	Coaxitron	Power Source	OSD	IP Rate	Size(mm)	ETC
Box Standard		JBX-2A950	1/2" Sony CMOS (IMX-385)	DC12V	-	1920 X 1080	-	2D + 3DNR <b>REAL WDR</b> Defog	UTC	12VDC	Built in	-	59.77 X 63.5 X 97.5	<b>Real Time True WDR (DOL)</b>

## ✓ 1/3" 2MP SONY Xarina EXMOR IP Camera Series

Type	Image	Model no.	Image Sensor	Video Compression	Lens	Max. Resolution	Max. Frame Rate	IR	Noise Reduction	Audio Direction	Audio Codec (Optional)	Power Source	Local Storage (Optional)	IP Rate	ETC
Box Camera		JBX-2IP950	1/2.8" Sony Exmor CMOS Sensor (IMX322)	H.264 & MJPEG Triple Stream	C/CS Mount	1920x1080	H.264 : 25, 30fps/1080p, M-JPEG : 25, 30fps/VGA	-	2D+3DNR D-WDR Defog Corridor mode	Full Duplex	Two way(G.711) - Optional	PoE(IEEE802.3af), 12VDC	Built in (Upto 128GB)	-	

## ✓ 1/3" 3MP SONY Xarina STARVIS IP Camera Series

Type	Image	Model no.	Image Sensor	Video Compression	Lens	Max. Resolution	Max. Frame Rate	IR	Noise Reduction	Audio Direction	Audio Codec (Optional)	Power Source	Local Storage (Optional)	IP Rate	ETC
Box Camera		JBX-3IP950	1/2.8" Sony Starvis CMOS Sensor (IMX124)	H.264 & MJPEG Triple Stream	C/CS Mount	2048x1536	H.264 : 25, 30fps/1080p, M-JPEG : 25, 30fps/VGA	-	2D+3DNR D-WDR Defog Corridor mode	Full Duplex	Two way(G.711) - Optional	PoE(IEEE802.3af), 12VDC	Built in (Upto 128GB)	-	Under Development